

PubliPress

Schwarz Produktion
MAXAU

PubliPress is a SC-A super calendered mechanical paper.

- High print evenness
- Suitable for rotogravure and heatset
- High print gloss

PRODUCER
Maxauer Papierfabrik GmbH

TYPICAL END USES
 Mass circulation magazines
 Supplements
 Catalogues
 Brochures
 Inserts
 Flyers

PRINTING METHODS
 HSWO
 Rotogravure

CHARACTERIZATION DATA
 Fogra 40

L* a* b* target values	L*	a*	b*	Flourescence (ISO 12647-2)
ISO 5631-3 (D50/C2°)	88	-1.1	5.2	Faint

ICC-PROFILE
SC_paper_eci.icc

TECHNICAL SPECIFICATIONS (target values)

Substance	g/m ²	45	49	52	56
Brightness	ISO 2470-2 (D65/10°)	%	66	66	66
CIE Whiteness	ISO 11476 (C/2°)	%	43	45	45
Opacity	ISO 2471	%	90	91	92
Gloss Hunter	ISO 8254-1	%	45	45	47
Thickness	ISO 534	µm	41	43	44
Bulk	ISO 534	cm ³ /g	0.8-0.9	0.8-0.9	0.8-0.9
Smoothness	ISO 8791-4 PPS (1MPa)	µm	1.0-1.2	1.0-1.2	1.0-1.2

REEL SPECIFICATIONS MAXAU

Cores: 76 mm & 150 mm
 Trimmed width: 7200 mm
 Width: min. 400 mm, max. 4320 mm
 Diameters: 1250 mm
 Weight: max. 6800 kg

CERTIFICATES
 EU Ecolabel DE/011/122
 Quality ISO 9001
 Environment ISO 14001
 EMAS
 Health & Safety ISO 45001
 Energy ISO 50001
 FSC®CoC
 PEFC™ CoC
 ISO 38200 CoC

ENVIRONMENT

Renewable fibre
 Recyclable paper
 Recyclable packaging materials

STORAGE AND HANDLING

- Store the paper in a humidity and temperature controlled area at 50% relative humidity and room temperature between 19°C and 23°C.
- If the paper is stored in non-air conditioned warehouse, it is absolutely necessary to allow a stabilisation period in the print room.
- Open the protective wrapping at the moment of use.